



## TCP GU10 BULBS

### Product Specifications

|              |      |
|--------------|------|
| Shape        | GU10 |
| CRI          | 80   |
| Mercury (Hg) | 0 MG |

|                     |                     |
|---------------------|---------------------|
| Start up time       | 0 Seconds           |
| Voltage / Frequency | 220-240 V / 50/60Hz |
| Lumen Cone          | 90°                 |

| Product code        | Tech | Cap  | Finish | Colour Temp (K) | Lumens (LM) | Nominal (W) | Actual (W) | EQ (W) | Energy Rating | Dimmable | Lifetime (Hrs) | Beam Angle | Dimensions (MM) | Pack Size | Barcode       |
|---------------------|------|------|--------|-----------------|-------------|-------------|------------|--------|---------------|----------|----------------|------------|-----------------|-----------|---------------|
| TCBLGU250W362527N2P | LED  | GU10 | White  | 2700            | 250         | 4           | 3.3        | 35     | F             | Non dim  | 25,000         | 36°        | 50 x 54         | 2         | 8720039600232 |
| TCBLGU250W362565N2P | LED  | GU10 | White  | 6500            | 250         | 4           | 3.3        | 35     | F             | Non dim  | 25,000         | 36°        | 50 x 54         | 2         | 8720039600249 |
| TCBLGU345W361527N2P | LED  | GU10 | White  | 2700            | 345         | 5           | 4.4        | 50     | G             | Non dim  | 15,000         | 36°        | 50 x 54         | 2         | 8720039607866 |
| TCBLGU345W361527N5P | LED  | GU10 | White  | 2700            | 345         | 5           | 4.4        | 50     | G             | Non dim  | 15,000         | 36°        | 50 x 54         | 5         | 8720039602038 |
| TCBLGU345W361565N2P | LED  | GU10 | White  | 6500            | 345         | 5           | 4.4        | 50     | G             | Non dim  | 15,000         | 36°        | 50 x 54         | 2         | 8720039602045 |
| TCBLGU345W361565N5P | LED  | GU10 | White  | 6500            | 345         | 5           | 4.4        | 50     | G             | Non dim  | 15,000         | 36°        | 50 x 54         | 5         | 8720039602052 |
| TCBLGU345G382565D2P | LED  | GU10 | Glass  | 6500            | 345         | 5           | 4.4        | 50     | F             | Dim      | 25,000         | 38°        | 50 x 54         | 2         | 8720039600263 |
| TCBLGU345G382527D2P | LED  | GU10 | Glass  | 2700            | 345         | 5           | 4.4        | 50     | F             | Dim      | 25,000         | 38°        | 50 x 54         | 2         | 8720039600256 |
| TCBLGU345G382527N2P | LED  | GU10 | Glass  | 2700            | 345         | 5           | 4.4        | 50     | F             | Non dim  | 25,000         | 38°        | 50 x 54         | 2         | 8720039602717 |
| TCBLGU345G382527N5P | LED  | GU10 | Glass  | 2700            | 345         | 5           | 4.4        | 50     | F             | Non dim  | 25,000         | 38°        | 50 x 54         | 5         | 8720039607835 |
| TCBLGU345G382565N2P | LED  | GU10 | Glass  | 6500            | 345         | 5           | 4.4        | 50     | F             | Non dim  | 25,000         | 38°        | 50 x 54         | 2         | 8720039607842 |
| TCBLGU345G382565N5P | LED  | GU10 | Glass  | 6500            | 345         | 5           | 4.4        | 50     | F             | Non dim  | 25,000         | 38°        | 50 x 54         | 5         | 8720039607859 |