



## TCP FLOODLIGHT WITH PIR MOTION SENSOR

Easy installation with a screwless terminal connector, made from recycled materials. IP44 rated for indoor/outdoor use, and has a tempered glass diffuser for enhanced durability.



**Quick Install**



**PIR Motion Sensor**



**IP44**



**Screwless Terminal**



**Mixed Recycle Materials**



**8m Sensor Range**

| Product Specifications | TCPLIGHT10WPIR8287      | TCPLIGHT20WPIR8290      | TCPLIGHT30WPIR8293      | TCPLIGHT50WPIR8296      |
|------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| PIR motion sensor      | Yes                     | Yes                     | Yes                     | Yes                     |
| Lumens                 | 1600 LM                 | 3200 LM                 | 4800 LM                 | 8000 LM                 |
| Colour temperature     | 4000K                   | 4000K                   | 4000K                   | 4000K                   |
| Power                  | 10w                     | 20w                     | 30w                     | 50w                     |
| IP rating              | IP44 / IK10             | IP44 / IK10             | IP44 / IK10             | IP44 / IK10             |
| Lifetime               | 30,000 Hours            | 30,000 Hours            | 30,000 Hours            | 30,000 Hours            |
| Dimmable               | Non dimmable            | Non dimmable            | Non dimmable            | Non dimmable            |
| Beam angle             | 120°                    | 120°                    | 120°                    | 120°                    |
| CRI                    | 70                      | 70                      | 70                      | 70                      |
| Energy rating          | C                       | C                       | C                       | C                       |
| Voltage / Frequency    | 220-240 V / 50/60Hz     | 220-240 V / 50/60Hz     | 220-240 V / 50/60Hz     | 220-240 V / 50/60Hz     |
| Dimensions             | W 130 x D 89 x H 170 MM | W 130 x D 89 x H 170 MM | W 185 x D 89 x H 192 MM | W 218 x D 89 x H 215 MM |
| Barcode                | 8720039606654           | 8720039606944           | 8720039607590           | 8720039607613           |